



Förstoring Mässing PG - PG

Specifikation

MATERIAL	Förnicklad mässing (CuZn39Pb3)
TEMPERATUROMRÅDE	-60°C...+200°C
FÄRG	Förnicklad Mässing
HALOGENFRI	Ja

Varianter

E-NUMMER	YTTERGÅNGA	INNERGÅNGA	L MM	L1 MM	Ø D MM	Ø D1 MM	L2 MM	L3 MM	ANTAL/FÖRP
709	PG7/12,5	PG9/15,2	5	15	10	17	9	7	100
1464550	PG9/15,2	PG11/18,6	6	16,5	12	20	9,5	7	100
913	PG9/15,2	PG13,5/20,4	6	17,5	12	22	10,5	7,5	100
1464551	PG11/18,6	PG13,5/20,4	6	17,5	15	22	10,5	8	100
1464552	PG11/18,6	PG16/22,5	6,5	19	15	24	11,5	8,5	100
1121	PG11/18,6	PG21/28,3	6,5	21	15	30	13	10	100
1464554	PG13,5/20,4	PG16/22,5	6,5	19	17	24	11,5	7,5	100
1321	PG13,5/20,4	PG21/28,3	6,5	21	17	30	13	8,5	100
1464556	PG16/22,5	PG21/28,3	6,5	21	18,5	30	13	8,5	100
1629	PG16/22,5	PG29/37,0	6,5	22,5	18,5	39	14,5	11	50
1464558	PG21/28,3	PG29/37,0	7	23	24	39	14,5	11,5	50
1464560	PG29/37,0	PG36/47,0	8	27,5	32	50	17,5	12	25
1464562	PG36/47,0	PG42/54,0	9	31	42	57	20	15	10
1464564	PG42/54,0	PG48/59,3	10	33	48	64	21	17	10